

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
19 July 2001 (19.07.2001)

PCT

(10) International Publication Number
WO 01/51974 A2

(51) International Patent Classification⁷: **G02B 6/38**

(21) International Application Number: PCT/GB01/00038

(22) International Filing Date: 5 January 2001 (05.01.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0000415.0 11 January 2000 (11.01.2000) GB

(71) Applicant (for all designated States except US): **BAE SYSTEMS PLC** [GB/GB]; Warwick House, P.O. Box 87, Farnborough Aerospace Centre, Farnborough, Hampshire GU14 6YU (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ALDRIDGE, Nigel, Bruce** [GB/GB]; 7 Russet Court, Kingswood, Wotton-u-Edge, Gloucestershire GL12 8SG (GB). **PROUDLEY, Geoffrey, Martland** [GB/GB]; Primrose Cottage, 3 Bradley Green, Wotton-u-Edge, Gloucestershire GL32

7PP (GB). **FOOTE, Peter, David** [GB/GB]; Warren Fields Farm, Trellech, Monmouth NP25 4PQ (GB). **READ, Ian, James** [GB/GB]; 25 Yew Tree Drive, Kingswood, Bristol BS15 4UA (GB).


(74) Agent: **FLETCHER WATTS, Susan, Jane**; BAE Systems PLC, Group IP Department, Farnborough Aerospace Centre, Lancaster House, P.O. Box 87, Farnborough, Hampshire GU14 6YU (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: IMPROVEMENTS RELATING TO INTERFACING EMBEDDED OPTICAL TRANSMISSION STRUCTURES



(57) Abstract: A method of and an apparatus for coupling a first optical transmission means (10, 42), such as an optical fibre, embedded within an aircraft composite (12, 40) to a second optical transmission means (14), such as an optical fibre, external to the composite (12, 40) is described. The method comprises locating the position of the first optical means (10, 42) embedded within the composite (12, 40) using X-ray scanning for example; forming a passageway (20, 62) by laser machining or drilling within the composite (12, 40) to the first optical transmission means (10, 42); and establishing an optical connection between the first and second optical transmission means (10, 42, 14) at the intersection of the passageway (20, 62) and the first optical transmission means (10, 42).

WO 01/51974 A2



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Improvements Relating to Interfacing Embedded Optical Transmission Structures.

The present invention concerns improvements relating to interfacing optical transmission structures and more particularly, thought not exclusively, to a method of and an apparatus for coupling a first optical transmission means, such as an optical fibre, embedded within a composite such as an aircraft panel to a second optical transmission means, such as an optical fibre, external to the composite. The present invention also concerns such a method or apparatus which can provide a coupling in a minimal number of steps thereby simplifying the coupling procedure.

The phrase 'embedded within a composite' in the context of the present invention is intended to mean that, at a possible point of connection, the article is completely surrounded by the composite and is located beneath the exterior surfaces of the composite after manufacture. Such an embedded article is not exposed to the exterior surface and can only be accessed by entering the interior of the composite.

The term 'composite' as used herein is to be construed broadly, in that it is directed to any support structure for carrying a light transmission means. Typical composites are aircraft panels, and other supportive structures made from plastics materials, carbon fibre, glass or metal for example and include multi-layer structures.

The use of optical fibres and advanced composites is becoming more accepted in the aircraft industry over the previous systems of lightweight metals and electrical wiring. There are many advantages to the use of optical fibres, such as reduced weight, elimination of electromagnetic problems, such as noise pick up and incidental radiation of signals, lower raw material costs, and elimination of potentially dangerous conductive paths. Whilst these advantages are clearly desirable, the use of optical systems in aircraft has its own specific characteristics, different to those associated with conventional systems, which have to date slowed acceptance of this new technology.

Fibre optics embedded in composite structures can provide elegant distributed and embedded sensing functions (e.g. of strain, temperature) as well as the potential for embedded communications links. Despite the proven functionality of such embedded optical fibre

structures, problems remain as to the best way of interfacing (i.e. launching and extracting light) to/from the embedded optical fibres. One way, described in US 5,299,273, involves attaching a relatively large optical connector to a composite laminate part having an optical fibre embedded therein. The optical connector is attached by trimming the structure across the path of the optical fibre thereby exposing an end of the fibre that lies flush with the surface of the structure. Then the optical fibre is polished and the connector is fitted using micro-positioning techniques to correctly align the connector and optical fibre.

Other current solutions include allowing delicate embedded fibres to emerge from the structure surface or edge (so called 'flying leads'), or embedding fibre connectors in a surface of the composite at the ends or sides of embedded optical fibres for subsequent connection to external optical devices or other optical fibres. Examples of the latter type of coupling are shown in US 5,809,197 and in the paper by S. Meller, J. Greene, C. Kozikowski, K. Murphy, R. Claus, "Polymer and Metal-Matrix Composite-Embedded Optical Fibres for Avionics Communications Links," SPIE Proceedings, Vol. 3042, pp. 383-388, 1997.

The provision of 'flying leads' is problematical in that these are potential single points of failure during use of the composite. As well as being prone to damage, the fibres must be managed during composite manufacture (lay-up) which will increase manufacturing complexity, time and cost. Likewise, the provision of conventional embedded connectors at the composite surface can also complicate the manufacturing process particularly since these embedded connectors tend to be rather bulky and require careful protection. Additionally, resin accretion can occur round these connectors (and also in the case of flying leads) which can lead to embrittlement and contamination effects.

Generally, all of the above methods suffer from the problems of potential damage to the optical fibres emerging out of the composite and to the embedded connectors present at the surface of the composite when the composite needs to be 'finished' in its manufacturing process. These problems have hindered the universal acceptance of embedded optical fibre systems within the aircraft industry.

It is desired to overcome or at least substantially reduce the above described problems.

The present invention resides in the appreciation that the embedded optical fibres or the optical connectors need not be exposed at a surface of the composite until after manufacturing processes, such as trimming and routing, on the composite have been completed. Once these manufacturing processes are complete, the embedded optical fibre or optical connector can be located and a passageway to it formed in the composite. In this way, the above described problems can be substantially alleviated.

More specifically, according to one aspect of the present invention there is provided a method of coupling a first optical transmission means embedded within a composite to a second optical transmission means external to the composite, the method comprising: locating the position of the first optical means embedded within the composite; forming a passageway within the composite to the first optical transmission means; and establishing an optical connection between the first and second optical transmission means at the intersection of the passageway and the first optical transmission means.

The present invention allows the optical transmission means to be hidden (inaccessible) within the composite, until such time as required, namely post manufacture of the composite. Then access to the transmission means can be recovered as required. This concept of complete embedment and recovery, post-manufacture also advantageously allows redundancy to be built into the composite. Spare embedded optical transmission means and/or interface optics could be embedded within the composite but remain hidden in the structure until required, for example if an existing optical transmission means and/or interface becomes damaged. These links would also be hidden at the time of manufacture of the composite and require no external management of delicate trailing leads for example. When a new optical communication channel or sensing function is required, the location of a selected transmission means can be detected and an appropriate passageway to the transmission means formed for access thereto. Accordingly, additional links and/or sensing functions can be provided without the need for additional optical transmission means external to the composite.

The present invention also provides benefits in terms of reduced manufacturing complexity, time and cost. The total number of operations required to establish a connection may also be

reduced as compared to the conventional systems. Furthermore, it is considered that the present invention will speed the implementation of embedded optical fibre systems in the aerospace industry.

5 The method may further comprise providing a high-quality optical interface surface at the intersection of the passageway and the first optical transmission means. This is preferably provided at the time when the first optical transmission means is embedded within the composite. The term 'high-quality optical interface surface' as used in the present invention is intended to denote a surface which can be coupled to another optical surface and provide an
10 acceptable optical interface (having an acceptably low level of signal loss) without the need for quality enhancing measures such as polishing of the surface. By providing such a high-quality surface, the interconnection to the first optical transmission means is made simpler in that there is no need to provide extra processing steps, such as polishing, to create an acceptable quality optical interface for light transmission.

15 The step of forming a passageway may comprise drilling or machining through the composite from an exterior surface thereof to the first optical transmission means and severing the first optical transmission means. This is one of the simplest ways of creating a passageway in a composite using readily available tools. In this case, the step of providing an optical interface
20 surface preferably comprises polishing a severed portion of the first optical transmission means. The polishing step is necessary to transform the severed portion of the first optical transmission means into a high-quality optical interface.

The step of forming a passageway may comprise: drilling or machining through the
25 composite to the first optical transmission means; providing the passageway with a protective plug for closing the passageway; and removing the protective plug prior to the step of forming an optical connection. In this way, access to the first optical transmission means advantageously can be established prior to completion of any manufacturing processes on the composite and the passageway and first optical transmission means can be protected by the
30 provision of the plug.

Preferably, the step of forming a passageway comprises irradiating an exterior surface of the composite using a laser (appropriate for machining the particular composite) to access the

first optical transmission means. In addition, the laser irradiation step preferably comprises using an Excimer laser. Laser irradiation advantageously provides a highly accurate way of forming a passageway in the composite to the first optical transmission means. Furthermore, using an Eximer laser means that the passageway can be formed with a reduced composite heating effect.

The step of forming a passageway may comprise using a depth marker to indicate when the passageway has been formed to the correct depth. This is particularly useful in laser machining where the light used for ablation can also be monitored for reflection to determine when a reflective marker representing a correct depth has been reached.

When using a laser, the method may further comprise preventing light used in the laser irradiation step from being optically coupled with the first optical transmission means. The purpose of such a step is to prevent any damage occurring to the first optical transmission means which may be caused by the wavelength of the laser radiation.

In this regard, the preventing step preferably comprises differentiating between the wavelengths of the light used in the laser machining step and the light used in the first optical transmission means, and preventing transmission of light used in the laser machining step to the first optical transmission means. This provides a way of preventing optical coupling between the laser light and the first optical transmission means which advantageously uses a minimal number of components. The two wavelengths can be differentiated e.g. by a wavelength selective mirror or beam splitter. Once the two wavelengths of light can be differentiated, one simple preferred way of preventing further optical coupling is for the preventing step to comprise allowing the light used in the laser machining step to be transmitted to at least one light beam absorbing means provided within the composite.

In order to determine the location of the first optical transmission means, the locating step may comprise using an embedded detectable position marker to indicate the location of the first optical transmission means within the composite. This is useful when the material of the composite and the first optical transmission means are not easily differentiated by the locating step.

In an embodiment of the present invention, the depth marker comprises the position marker and hence the number of additional components is advantageously reduced. Also, the position marker or the depth marker may comprise a sacrificial coating and the laser irradiation step
5 may further comprise removing the coating after formation of the passageway to access the first optical transmission means. In this way, the precise depth of the passageway can be controlled with high accuracy.

The step of locating the position of the first optical transmission means or the step of forming
10 a passageway may comprise locating the position of the position marker or the depth marker within the composite using an imaging technique. In this way, a map of the location of the first transmission means can be determined for the subsequent passageway formation. Preferably, the imaging technique comprises an X-ray imaging process. This non-invasive method is highly discriminatory and can distinguish between optical fibres and carbon fibre
15 or plastics composites, for example.

Regarding the interconnection interface, the step of establishing an optical connection may comprise providing a thermal expanded core optical fibre at the optical interface surface. This reduces the alignment constraints at the point of interconnection thereby easing the
20 interconnection process.

The method may further comprise aligning an interface means within the passageway to be in optical communication with first optical transmission means at the interface surface, and arranging for the interface means to be accessible to the second optical transmission means.
25 The interface means enables the first and second optical transmission means to be optically interconnected and movement of the interface means provides readily adjustable interconnection alignment between the first transmission means and the second transmission means.

Preferably, the aligning step comprises using an alignment structure embedded within the
30 composite to align the interface means with the first optical transmission means. This advantageously speeds up the interconnection process as an accurate interconnection can be without undue delay which may otherwise be caused by alignment procedures.

The method may further comprise forming the alignment structure embedded within the composite using an X-ray lithographic technique. This technique simplifies three-dimensional structure formation in that no special tools and machining skills are required to create the structures. Rather, they can be created under computer control with exceptional repeatability.

The method may further comprise optically processing light to or from the first optical transmission means by an optical processing means embedded within the composite and optically connected to the first optical transmission means. Whilst there is always some loss with an optical coupling, the optical processing can enhance a signal at the optical interface to improve the efficiency of the optical coupling. In addition, the light from the first transmission means can be manipulated to optimise its extraction from the composite. For example, the step of optically processing light may comprise steering a light beam. More specifically, the steering step may comprise using a beam splitter or a micro-turning mirror. Also the step of optically processing light may comprise collimating a light beam and the light beam collimating step may comprise using a graded index lens or a graded index fibre. All of these different ways of manipulating the light beam can advantageously configure the interfacing process to optimise transmission characteristics regardless of the desired location of input/output to/from the composite.

The method may further comprise providing the optical processing means on a micro-substrate and securing the first optical transmission means to the optical processing means using the micro-substrate. This advantageously provides a secure, strain-relieving connection between the optical processing means and the first optical transmission means. Furthermore, the orientation of the optical processing means can be controlled as the micro-substrate may be more readily alignable than the optical processing means itself.

The method may further comprise providing the alignment structure on the micro-substrate. In this way, a single micro-structure need only be prepared to implement several functions without the need for other specialist structures. This advantageously reduces costs.

The first optical transmission means may comprise an elongate structure and the step of establishing an optical connection may be effected to a side of the elongate structure. In this

case, the step of providing an optical interface surface preferably comprises providing a first evanescent coupling means optically connected to the first optical transmission means. This is an efficient way of dividing out some of the optical signal from the first optical transmission means to the second optical transmission means.

5

Preferably, the step of establishing an optical connection comprises providing a second evanescent coupling means optically connected to the second optical transmission means and aligning the second evanescent coupling means with the first evanescent coupling means. Providing mutually co-operating evanescent couplings maximises the efficiency of the coupling process.

10

The first and second optical transmission means preferably comprise optical fibres because these are some of the most cost-effective and efficient optical transportation systems currently available.

15

Micro-optical components or an assembly of components are preferably completely embedded along with the fibre at the time of manufacture. The micro-optics package could be based on a number of technologies. GRIN (Graded Index) lenses or fibres could be interfaced (e.g. spliced) to the embedded system fibre to provide beam collimation (for eased alignment to the other half of the interface).

20

It is necessary to 'find' the buried micro-optics with the machining laser (or alternative process). However, the target site could be readily identified prior to machining by embedding structures (e.g. metallic coatings) that would be visible on X-ray of the composite.

25

It is possible to use TEC optical fibres, possibly spliced to the embedded optical fibre or formed at the end of the system fibre to expand the core of the embedded fibre to relax alignment constraints.

30

The present invention enables a composite to be formed with embedded optical fibres and micro-optical components. The composite can be processed through any number of manufacturing steps until a finished composite is created. Then by X-ray imaging of the composite, the location of the optical fibres and/or any micro-optical components can be

determined and markings can be provided for subsequent use on the composite. These markings represent drilling points for accessing the embedded optical fibres and/or micro-optical components.

- 5 According to another aspect of the present invention there is provided an optical coupling for connecting a first optical transmission means embedded within a composite to a second optical transmission means external to the composite, the coupling comprising: means for locating the position of the first optical transmission means embedded within the composite; a passageway formed within the composite to the embedded first optical transmission means;
10 and an optical connection established between the first and second optical transmission means at the intersection of the passageway and the first optical transmission means.

Presently preferred embodiments of the present invention will now be described with reference to the accompanying drawings. In the drawings:

15

Figures 1a, 1b and 1c are schematic partial sectional views of an aircraft composite incorporating an optical fibre showing different stages of a method of interfacing to the embedded optical fibre according to a first embodiment of the present invention;

- 20 Figures 2a and 2b are schematic partial sectional views of aircraft composites each incorporating an optical fibre and an embedded optical port according to respective second and third embodiments of the present invention;

- Figure 3a is a schematic partial sectional view of an aircraft composite incorporating an optical fibre and an embedded optical port according to a fourth embodiment of the present
25 invention;

Figure 3b is a schematic partial sectional view the aircraft composite of Figure 3a showing a method of forming a laser machined passageway to the embedded optical port;

30

Figure 4a is a schematic perspective view of an optical fibre in a polishing block which is used to prepare the optical fibre for side coupling in a fifth embodiment of the present invention;

Figure 4b is a schematic sectional view of the polishing block and optical fibre of Figure 4a along the length of the polishing block;

5 Figures 5a, 5b and 5c are schematic partial sectional views of an aircraft composite incorporating the polished optical fibre of Figures 4a and 4b showing different stages of a method of interfacing to the embedded optical fibre according to the fifth embodiment of the present invention;

10 Figure 6a a schematic sectional view in a vertical plane of an aircraft composite incorporating an optical fibre and an embedded optical port according to a sixth embodiment of the present invention; and

15 Figure 6b a schematic sectional view in a horizontal plane of the aircraft composite of Figure 6a according to the sixth embodiment of the present invention.

Referring to Figures 1a, 1b and 1c, a method of coupling an optical fibre 10 embedded within a carbon fibre aircraft composite 12 to another optical fibre 14 provided externally of the composite 12 according to a first embodiment of the present invention, is now described. The
20 optical fibre 10 is embedded at the time of manufacture of the composite 12 and is effectively hidden from the exterior surfaces 16 of the composite 12 at all possible points of connection as the optical fibre 10 does not extend to a connection surface 16 of the composite 12. In this way, the connection surfaces 16 of the composite 12 can be finished in the manufacturing process without damaging the optical fibre 10.

25

Figure 1a shows one end 17 of the aircraft composite 12, having the optical fibre 10 embedded therein, which has been through the finishing processes of manufacturing. Although not shown, the other end of the composite 12 may be similar to that shown in Figure 1a. In order to form an optical connection to the embedded optical fibre 10, the
30 composite 12 is scanned by X-rays and the results thereof establish the exact location of the optical fibre 10 within the composite 12. It is not necessary to provide any special detection feature of structure within the composite, as the location of the optical fibre can be readily determined. If image enhancement of the embedded structure is required, selective fibre

coating (prior to embedment) could be used. The results are used to determine a drilling point 18 for creating access to the buried optical fibre 10 from the exterior of the composite 12.

5 Access to the buried optical fibre is established in the composite 12 by drilling a hole (passageway) 20 from the determined drilling point 18 through the composite 12 as shown in Figure 1b. Hole drilling is an accepted production practice and is routinely performed in composite manufacturing. The thus formed passageway 20 intersects the optical fibre 10 and severs it. In order to reinstate an optical finish on the face of the optical fibre 10, namely to form a high-quality optical interface at the severed portion 22 of the optical fibre 10, the
10 severed portion 22 is then polished using a standard polishing process which requires no further explanation herein. However, it is to be appreciated that the polishing process is carried out from within the passageway 20.

A plug connection is then made to the polished end 24 of the severed optical fibre 12 as
15 shown in Figure 1c. More particularly, a connector plug 26 having an internal optical transmission path 28 is inserted in the passageway 20 and positioned so as to optically align one end of the transmission path 28 with the polished severed end 24 of the optical fibre 10. The connector plug 26 functions to introduce/extract light to/from the embedded optical fibre 10 via the internal optical transmission path 28. Any alignment technique can be used, but in
20 the present embodiment, alignment is built into the connector plug 26 by use of a three-axis translation micropositioning mechanism (not shown) which moves the internal optical transmission path 28 to maximise the coupling before fixing the relative position of the path and the plug 26 in the passageway and hence the optical alignment.

25 An interface connector 30 is optically coupled to the other end of the internal optical transmission path 28 of the connector plug 26. In its connected state as shown in Figure 1c, an internal optical path 32 within the interface connector 30 leads from the connector plug 26 to the external optical fibre 14 which is attached to the interface connector 30. In this way, an optical connection between the embedded optical fibre 10 and the external optical fibre 14
30 can be established.

Whilst the connection between the embedded optical fibre 10 and the external optical fibre 14 has been shown at one end 17 of the composite 12, the above described connection procedure

could be carried out at both ends of the composite 12. This procedure would connect external optical fibres 14 to either ends of the embedded optical fibre 10 which has no portion emerging from any exterior surface 16 of the composite 12. In this way, an optical fibre 10 completely encased within a composite 12 can be used for the transmission of optical signals or the sensing of environmental conditions to which the composite is exposed.

In an alternative embodiment (not shown) to the above described first embodiment, alignment constraints can be eased by using an expanded core fibre, such as a TEC (Thermally Expanded Core) optical fibre, at the interface site where the embedded optical fibre 10 has been severed. More particularly, the TEC optical fibre is spliced onto the optical fibre 10 and embedded within the composite. When the composite is scanned, the X-ray results identify the TEC optical fibre portion and the location of the drilling point 18 is set to create a passageway which will intersect this portion.

Referring to Figure 2a, a second embodiment of the present invention is now described. As there are many similarities between this embodiment and the first embodiment, the following description will be directed to the differences between these embodiments to avoid unnecessary repetition.

A composite panel 40 including an embedded optical fibre 42 is used. The optical fibre 42 has a micro-optical component 44 provided at one end thereof which is also completely embedded within the composite panel 40 at the time of its manufacture. The micro-optical component 44 comprises e.g. a GRIN (Graded Index) lens which is bonded fused to the embedded optical fibre 42 to provide beam collimation for eased alignment with another half of the interface (plug connector 26 and interface connector 30 as in the first embodiment). Alternatively, the GRIN lenses can be replaced by an appropriate length of GRIN (Graded Index) fibre.

Prior to finishing of the manufacturing processes on the composite panel, the location of the micro-optical component 44 is determined by use of an imaging technique such as X-ray scanning and a passageway 46 to the micro-optical component 44 is formed, by drilling for example. The passageway 46 in this embodiment is formed in-line with the micro-optical component 44 via an end face of the composite 40. The thus formed passageway 46 is then

temporarily sealed with a protective plug 48 to protect the embedded micro-optical component 44 from the subsequent composite finishing processes. Once the finishing processes have been completed, the plug 48 can be removed to provide access to the buried micro-optical component 44 and hence the embedded optical fibre 42. Removal of the plug 48 thereby provides an interface port to the embedded optical fibre 42 via an embedded high-quality optical surface 50 provided by the micro-optical component 44. Links to the outside world are then installed using a connector plug and interface connector (not shown) as in the first embodiment. The formation of ports could be performed after composite finishing, where the plugs merely provide protection of the interface until some later time when the connection is made.

If required, the high-quality optical surface 50 can be covered with a protective coating (not shown) which is removable by chemical etching for example, just prior to forming the optical connection. In addition, whilst GRIN lenses have been used in the above described embodiment, it is also possible to replace these with GRIN fibres that perform essentially the same operation.

A third embodiment of the present invention is now described with reference to Figure 2b. The third embodiment is very similar to the second embodiment and, accordingly, to avoid unnecessary repetition, only the differences will be discussed hereinafter.

In the third embodiment, it is desired to connect to the embedded optical fibre 42 from an upper side face 52 of the composite 40. Accordingly, the micro-optical component 44 is provided with a micro-turning mirror 54 for controllably steering the direction of light emitted from the embedded optical fibre 42 via the micro-optical component 44. In the present embodiment, the light is reflected and turned through 90° using the micro-turning mirror 54 having a 45° mirror angle. As the resultant light beam is steered towards the upper side surface 52 of the composite 40, a passageway 56 is provided from the upper side surface 52 of the composite 40 to the micro-turning mirror 54. The passageway 56 is then sealed with the protective plug 48 until the manufacturing processes being carried out on the composite 40 have been completed as in the previously described second embodiment.

An alternative light beam processing element to the micro-turning mirror 54, which could be used if required to provide beam steering, is a beam splitter (not shown). Other micro-optical structures that could be embedded include gratings, wave-guides, evanescent couplers, wave-plates, holograms and optical filters. These structures could be involved in system
5 interrogation as well as providing an optical interface.

Referring now to Figure 3a, a fourth embodiment of the present invention is now described. The fourth embodiment is similar to the third embodiment described above and accordingly only the differences will be described hereinafter. In this embodiment, the composite is
10 manufactured and finished without any pre-formed and plugged passageway to the optical processing element. Rather, the passageway is only formed after manufacture of the composite has been fully completed. More specifically, the composite panel 40 comprises an embedded optical fibre 42, beam collimating micro-optical component 44 and a beam turning mirror 54 as in the third embodiment. However, the turning mirror 54 has specific
15 wavelength selectivity as will be described in detail later. The composite also comprises a machining beam stop 58 provided at an underside of the turning mirror 54 and a metallic position marker 60 which is readily detectable by an imaging technique.

Once the composite has been completed, it is X-rayed to determine the precise location of the
20 position marker 60. A drilling point (not shown) is determined and marked on the composite surface. Then a precision laser machining technique as illustrated schematically in Figure 3b is used to create a passageway 62 from the drilling point through the composite 40 to the position marker 60 and the turning mirror 54. An Eximer laser (for example) together with focusing optics 64 are used as it allows accurate and controlled ablation of composite panel
25 material (e.g. carbon fibre) on a pulse by pulse basis.

This approach requires protection of the embedded optical fibre 42 and micro-optical component 44 to ensure that they are not damaged during the laser machining process. Accordingly, the top surface of the turning mirror 54 is provided with a protective sacrificial
30 coating 66 that can be removed by the Eximer laser after the passageway 62 has been formed. The coating 66 is metallic and aids the machining process because the light reflectivity of the bottom of the passageway 62 is monitored during its formation such that it is possible to determine when this coating 66 had been reached, namely when the passageway is at the

correct depth. Then the laser can be set to remove a predetermined thickness of material corresponding to the thickness of the protective coating. Alternatively, the coating can be made of a material such as copper which can be selectively ablated by the laser (due to specific light wavelength absorption characteristics) or selectively chemically etched without
5 damaging the surfaces of the carbon fibre composite 40. In modification to the present embodiment, the position marker (target) 60 can be omitted and the metallic coating 66 can provide its function as it is readily detectable by the X-ray imaging technique.

In the present embodiment, the optical transmission wavelengths and laser machining
10 wavelengths are selected to be different. Also, the turning mirror 54 has a wavelength selective reflectance characteristic to ensure that the machining laser radiation is not coupled into the embedded optical fibre 42. More specifically, the turning mirror 54 has a characteristic which transmits the laser machining wavelengths of light and reflects the optical transmission wavelengths of light. The absorbing beam stop 58 is positioned so as to
15 absorb the laser radiation once it has created the passageway 62 and has been transmitted through the turning mirror 54.

Once the passageway 62 has been created, the connection to the embedded optical fibre 42 is carried out in a similar manner to that described in the previous embodiments.

20 A fifth embodiment of the present invention is now described with reference to Figures 4a, 4b, 5a, 5b and 5c. In this embodiment, the coupling to an optical fibre 70 is effected to a side portion thereof to form a so called evanescent coupling. The purpose of having evanescent coupling is that it enables a branching structure to be created such that the signal being
25 transmitted along the optical fibre 70 can be split between the existing embedded optical fibre 70 and another optical fibre 72 external to a composite 74 in which the fibre 70 is provided. This form of coupling is used to allow side-access to fibres in an efficient way.

Figures 4a and 4b show a pre-conditioning procedure employed for creating a side coupling
30 to the optical fibre 70. The procedure involves placing the optical fibre 70 in a polishing block 76 which is arranged to retain the optical fibre 70 with a side portion 78 slightly protruding from a polishing surface 80 of the block 76. The protruding side portion 78 of the

optical fibre 70 is then polished using any standard polishing technique which is well known to the skilled addressee.

Once the side portion has been polished, the optical fibre 70 is embedded within the composite 74 in such a way as to facilitate coupling to the polished portion 78. More particularly, as can be seen clearly in Figure 5a, an embedded evanescent coupler block 82 is provided at the polished side region 78 to provide support for the optical fibre 70 at the predetermined point of connection. The optical fibre 70 and the coupler block 82 are embedded within the composite 74 such that any manufacturing processes acting on the exterior surfaces of the composite do not cause any effect to the optical fibre 70 or the coupler block 82.

In this embodiment, the coupler block 82 also acts as a post-manufacture position locator for a coupling point and is easily detected by the results of an X-ray scan of the composite 74. Once the scan is completed, a machining point is determined for machining down to the coupler block 82 and the composite 74 is machined to create a shallow passageway 84 for access to the polished side portion 78 of the optical fibre 70 as shown in Figure 5b.

The thus formed passageway 84 is of a size sufficient to house an evanescent interface coupler block 86. The interface coupler block 86 supports an end of the external optical fibre 72 which also has a polished side surface. In order to effect coupling, the interface coupler block 86 and the coupler block 82 are connected together to optically align the respective polished side portions of their optical fibres 70, 72.

In another embodiment (not shown), the optical fibres 70, 72 with polished side portions are replaced by D-fibres in the composite 74. D-fibres are similar to side polished fibres and have a flat side close to the fibre core which gives them a reduced alignment tolerance compared to other optical fibre geometries. At a region of connection, the D-fibres are provided with support blocks for ease of interfacing.

A sixth embodiment of the present invention, as shown in Figures 6a and 6b, is now described. This embodiment is also very similar to the previously described fourth

embodiment and, so to avoid unnecessary repetition, only the differences are described hereinafter.

The principle difference is that, for ease of manufacture, the micro-optical component 90 is formed on a micro-substrate 92 that is also embedded within the composite panel 94. The micro-substrate 92 is formed from silicon though alternatively other materials can be used. The machining of silicon is relatively easy and enables connecting structures such as grooves, pockets, reflectors and alignment markers (not shown) to be formed. These connecting structures perform two connectivity functions. Firstly they enable the micro-optical component 90 and the optical fibre 96 to be aligned and secured together with high precision on the micro-substrate 92, and secondly, they enable the combination of the micro-optical component 90 and embedded optical fibre 96 to be coupled to the external connector (not shown) accurately and reliably. The micro-substrate 92 is embedded at the time of composite manufacture.

The micro-optical component 90 can comprise lenses/optics/prisms as well as windows or coatings to protect their optical surfaces prior to being exposed for connection. All of the assembly is embedded during manufacture. It can also include target markers for X-ray/C-scan location of the assembly.

A process that can be used to create alignment structures for the micro-optical components 90 is the so called LIGA (Lithographie Galvanoformung and Abformung) process which is based on X-ray lithography. This process uses deep X-raying of a resist layer and subsequent electroplating to form accurately aligned structures. This can provide alignment structures in metals and ceramics and (from a master structure) allow high-volume replication in other materials such as composites manufactured out of strong plastics materials such as PMMA (Polymethylmethacrylate) and PEEK (Polyethylene terephthalate). The substrate 92 can be formed from various processes, this is but one. Other processes include etching of silicon or laser machining. The aligned substrate 92 and micro-optical components 90 are designed to be rugged enough to survive both the manufacturing process and the operational environment of the aircraft/composite structure.

Some optical processing elements, especially those without rotational symmetry may be susceptible to misalignment during the composite cure process. A substrate containing these elements would minimise such movement. The natural ply structure of the composite material may also make the substrate lie 'flat' further improving alignment to other structures.

5

Other micro-optical structures that could be used as the beam processing elements in the above embodiments include gratings, wave-guides, evanescent couplers, wave-plates, holograms and optical filters. These structures could be involved in system interrogation as well as providing an optical interface.

10

Having described particular preferred embodiments of the present invention, it is to be appreciated that the embodiments in question are exemplary only and that variations and modifications such as will occur to those possessed of the appropriate knowledge and skills may be made without departure from the spirit and scope of the invention as set forth in the appended claims. For example, whilst X-ray imaging is a preferred way of detecting the location of the embedded optical fibre and/or the micro-optical components, other techniques may also be suitable such as ultrasonic imaging. Also, the use of a substrate can equally well be used to align an optical fibre to an evanescent or D-fibre coupler.

15

CLAIMS:

1. A method of coupling a first optical transmission means embedded within a composite to a second optical transmission means external to the composite, the method comprising:
 locating the position of the first optical means embedded within the composite;
 forming a passageway within the composite to the first optical transmission means; and
 establishing an optical connection between the first and second optical transmission means at the intersection of the passageway and the first optical transmission means.
2. A method according to Claim 1, further comprising providing a high-quality optical interface surface at the intersection of the passageway and the first optical transmission means.
3. A method according to Claim 1 or 2, wherein the step of forming a passageway comprises drilling or machining through the composite from an exterior surface thereof to the first optical transmission means and severing the first optical transmission means.
4. A method according to Claim 3 as dependent on Claim 2, wherein the step of providing an optical interface surface comprises polishing a severed portion of the first optical transmission means.
5. A method according to any preceding claim, wherein the step of forming a passageway comprises: drilling or machining through the composite to the first optical transmission means; providing the passageway with a protective plug for closing the passageway; and removing the protective plug prior to the step of forming an optical connection.
6. A method according to Claim 1 or 2, wherein the step of forming a passageway comprises irradiating an exterior surface of the composite using a laser to access the first optical transmission means.
7. A method according to Claim 6, wherein the laser irradiation step comprises using an excimer laser.

8. A method according to Claim 6 or 7, further comprising preventing light used in the laser irradiation step from being optically coupled with the first optical transmission means.
9. A method according to Claim 8, wherein the preventing step comprises differentiating between the wavelengths of the light used in the laser machining step and the light used in the first optical transmission means, and preventing transmission of light used in the laser machining step to the first optical transmission means.
10. A method according to Claim 8 or 9, wherein the preventing step comprises allowing the light used in the laser machining step to be transmitted to at least one light beam absorbing means provided within the composite.
11. A method according to any preceding claim, wherein the step of locating the position of the first optical transmission means comprises using an embedded detectable position marker to indicate the location of the first optical transmission means within the composite.
12. A method according to any preceding claim, wherein the step of forming a passageway comprises using a depth marker to indicate when the passageway has been formed to the correct depth.
13. A method according to Claim 12 as dependent from Claim 11, wherein the depth marker comprises the position marker.
14. A method according to any of Claims 11 to 13 as dependent from any of Claims 6 to 10, wherein the position marker or the depth marker comprises a sacrificial coating and the laser irradiation step further comprises removing the coating after formation of the passageway to access the first optical transmission means.
15. A method according to any of Claims 11 to 14, wherein the step of locating the position of the first optical transmission means or the step of forming a passageway comprises locating the position of the position marker or the depth marker within the composite using an imaging technique.

16. A method according to Claim 15, wherein the imaging technique comprises an X-ray imaging process.
17. A method according to Claim 2 or any of Claims 3 to 16 as dependent from Claim 2, wherein the step of establishing an optical connection comprises providing a thermal expanded core optical fibre at the optical interface surface.
18. A method according to any preceding claim, further comprising aligning an interface means within the passageway to be in optical communication with first optical transmission means at the interface surface, and arranging for the interface means to be accessible to the second optical transmission means.
19. A method according to Claim 18, wherein the aligning step comprises using an alignment structure embedded within the composite to align the interface means with the first optical transmission means.
20. A method according to Claim 19, further comprising forming the alignment structure embedded within the composite using an X-ray lithographic technique.
21. A method according to any preceding claim, further comprising optically processing light to or from the first optical transmission means by an optical processing means embedded within the composite and optically connected to the first optical transmission means.
22. A method according to Claim 21, wherein the step of optically processing light comprises steering a light beam.
23. A method according to Claim 22, wherein the steering step comprises using a beam splitter or a micro-turning mirror.
24. A method according to any of Claims 21 to 23, wherein the step of optically processing light comprises collimating a light beam.

25. A method according to Claim 24, wherein the light beam collimating step comprises using a graded index lens or a graded index fibre.
26. A method according to any of Claims 21 to 25, further comprising providing the optical processing means on a micro-substrate and securing the first optical transmission means to the optical processing means using the micro-substrate.
27. A method according to Claim 26 as dependent on Claim 19 or 20, further comprising providing the alignment structure on the micro-substrate.
28. A method according to any preceding claim, wherein the first optical transmission means comprises an elongate structure and the step of establishing an optical connection is effected to a side of the elongate structure.
29. A method according to Claim 28, wherein the step of providing an optical interface surface comprises providing a first evanescent coupling means optically connected to the first optical transmission means.
30. A method according to Claim 29, wherein the step of establishing an optical connection comprises providing a second evanescent coupling means optically connected to the second optical transmission means and aligning the second evanescent coupling means with the first evanescent coupling means.
31. A method according to Claim 28, wherein the first optical transmission means and the second optical transmission means each comprise a D-fibre and the step of establishing an optical connection comprises aligning flat faces of the D-fibres together.
32. A method according to Claim 31, further comprising providing the D-fibres with support structures at the optical interface.

33. An optical coupling for connecting a first optical transmission means embedded within a composite to a second optical transmission means external to the composite, the coupling comprising:

means for locating the position of the first optical transmission means embedded within the composite;

a passageway formed within the composite to the embedded first optical transmission means; and

an optical connection established between the first and second optical transmission means at the intersection of the passageway and the first optical transmission means.

34. An optical coupling according to Claim 33, further comprising a high-quality optical interface surface provided at the intersection of the passageway and the first optical transmission means.

35. An optical coupling according to Claim 33 or 34, wherein the passageway comprises a drilled or machined orifice through the composite from an exterior surface thereof to the first optical transmission means to a depth sufficient to sever the first optical transmission means.

36. An optical coupling according to Claim 35 and dependant on Claim 34, wherein the optical interface surface comprises a polished severed portion of the first optical transmission means.

37. An optical coupling according to any of Claims 33 to 36, wherein the passageway comprises a drilled or machined orifice through the composite to the first optical transmission means; and a protective plug provided in the passageway for closing the passageway, the protective plug being removable prior to forming an optical connection.

38. An optical coupling according to Claim 33 or 34, wherein the passageway comprises a laser irradiated orifice through the composite to the first optical transmission means.

39. An optical coupling according to Claim 38, further comprising means for preventing light used in the formation of the laser irradiated orifice from being optically coupled with the first optical transmission means.
40. An optical coupling according to Claim 39, wherein the preventing means is arranged to differentiate between the wavelengths of the light used in the formation of the laser irradiated orifice and the light used in the first optical transmission means, and to block transmission of light used in the formation of the laser irradiated orifice to the first optical transmission means.
41. An optical coupling according to Claim 39 or 40, wherein the preventing means comprises at least one light beam absorbing means embedded at an appropriate position within the composite.
42. An optical coupling according to any of Claims 33 to 41, wherein the locating means comprises an embedded detectable position marker to indicate the position of the first optical transmission means within the composite.
43. An optical coupling according to any of Claims 33 to 42, further comprising a depth marker embedded within the composite to indicate when the passageway has been formed to the correct depth.
44. An optical coupling according to Claims 43 as dependent on Claim 42, wherein the depth marker comprises the position marker.
45. An optical coupling according to any of Claims 42 to 44 as dependent from any of Claims 38 to 41, wherein the position marker or the depth marker comprises a sacrificial coating which is arranged to be removable after the formation of the passageway to access the first optical transmission means.
46. An optical coupling according to Claim 45, wherein the coating comprises a reflective coating.

47. An optical coupling according to Claim 46, wherein the coating comprises a metallic coating.

48. An optical coupling according Claim 34 or any of Claims 35 to 47 as dependant from Claim 34, wherein the optical interface surface is provided at a thermally expanded core optical fibre connected to the first optical transmission means.

49. An optical coupling according to any of Claims 33 to 48, further comprising an interface means alignable within the passageway to be in optical communication with first optical transmission means at the optical interface surface, the interface means being arranged to be accessible to the second optical transmission means.

50. An optical coupling according to Claim 49, further comprising an alignment structure embedded within the composite for aligning the interface means with the first optical transmission means.

51. An optical coupling according to any of Claims 33 to 50, further comprising optical processing means embedded within the composite, the optical processing means being optically connected to the first optical transmission means for processing light to or from the first optical transmission means.

52. An optical coupling according to Claim 51, wherein the optical processing means comprises means for steering a light beam.

53. An optical coupling according to Claim 52, wherein the steering means comprises a beam splitter or a micro-turning mirror.

54. An optical coupling according to any of Claims 51 to 53, wherein the optical processing means comprises means for collimating a light beam.

55. An optical coupling according to Claim 54, wherein the light beam collimating means comprises a graded index lens or a graded index fibre.
56. An optical coupling according to any of Claims 51 to 55, wherein the optical processing means comprises at least one of the group comprising an optical grating element, a wave-guide, a wave plate, a hologram and an optical filter.
57. An optical coupling according to any of Claims 51 to 56, further comprising a micro-substrate on which the optical processing means is provided and secured to the first optical transmission means.
58. An optical coupling according to Claim 57 as dependent on any of Claims 51 to 56 as dependant from Claim 50, wherein the alignment structure is provided on the micro-substrate.
59. An optical coupling according to any of Claims 33 to 58, wherein the first optical transmission means comprises an elongate structure and the optical interface surface is provided at a side of the elongate structure.
60. An optical coupling according to Claim 59, wherein the optical connection comprises a first evanescent coupling means optically connected to the first optical transmission means.
61. An optical coupling according to Claim 60, wherein the optical connection comprises a second evanescent coupling means optically connected to the second optical transmission means and optically aligned with the first evanescent coupling means.
62. An optical coupling according to Claim 59, wherein the first optical transmission means and the second optical transmission means each comprise a D-fibre which are coupled together by aligning flat faces of the D-fibres together.
63. An optical coupling according to Claim 62, further comprising support structures for the D-fibres at the optical interface.

64. An optical coupling according to any of Claims 33 to 63, wherein the first and/or second optical transmission means comprises an optical fibre.

65. A method or optical coupling substantially as described hereinbefore with reference to the accompanying drawings.

Fig.1a.




Fig.1b.




Fig.1c.




Fig.2a.




Fig.2b.




Fig.3a.




Fig.3b.




Fig.4a.





Fig.4b.



5/6

Fig.5a.




Fig.5b.




Fig.5c.




Fig.6a.





Fig.6b.



THIS PAGE BLANK (USPTO)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
19 July 2001 (19.07.2001)

PCT

(10) International Publication Number
WO 01/51974 A3

- (51) International Patent Classification⁷: **G02B 6/36, B64C 1/00**
- (21) International Application Number: **PCT/GB01/00038**
- (22) International Filing Date: **5 January 2001 (05.01.2001)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data: **0000415.0 11 January 2000 (11.01.2000) GB**
- (71) Applicant (for all designated States except US): **BAE SYSTEMS PLC [GB/GB]; Warwick House, P.O. Box 87, Farnborough Aerospace Centre, Farnborough, Hampshire GU14 6YU (GB).**
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **ALDRIDGE, Nigel, Bruce [GB/GB]; 7 Russet Court, Kingswood, Wotton-u-Edge, Gloucestershire GL12 8SG (GB). PROUD-LEY, Geoffrey, Martland [GB/GB]; Primrose Cottage, 3 Bradley Green, Wotton-u-Edge, Gloucestershire GL32 7PP (GB). FOOTE, Peter, David [GB/GB]; Warren Fields Farm, Trellech, Monmouth NP25 4PQ (GB). READ, Ian, James [GB/GB]; 25 Yew Tree Drive, Kingswood, Bristol BS15 4UA (GB).**
- (74) Agent: **FLETCHER WATTS, Susan, Jane; BAE Systems PLC, Group IP Department, Farnborough Aerospace Centre, Lancaster House, P.O. Box 87, Farnborough, Hampshire GU14 6YU (GB).**
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR). OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).**
- Published:
— with international search report
- (88) Date of publication of the international search report:
27 December 2001
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **OPTICALLY CONNECTING EMBEDDED OPTICAL FIBERS IN COMPOSITE PANELS**



(57) Abstract: A method of and an apparatus for coupling a first optical transmission means (10, 42), such as an optical fibre, embedded within an aircraft composite (12, 40) to a second optical transmission means (14), such as an optical fibre, external to the composite (12, 40) is described. The method comprises locating the position of the first optical means (10, 42) embedded within the composite (12, 40) using X-ray scanning for example; forming a passageway (20, 62) by laser machining or drilling within the composite (12, 40) to the first optical transmission means (10, 42); and establishing an optical connection between the first and second optical transmission means (10, 42, 14) at the intersection of the passageway (20, 62) and the first optical transmission means (10, 42).

WO 01/51974 A3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 01/00038

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 G02B6/36 B64C1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G02B B64C B64D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 322 479 A (ADVANTEST CORP) 26 August 1998 (1998-08-26)	1-4, 18-24, 33-36, 49-52, 54, 59, 64, 65 5, 37
A	abstract; figures 4, 9, 10, 12 page 15, line 19 - page 16, line 21 page 11, line 18 - line 26 --- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

22 May 2001

Date of mailing of the international search report

20.08.01

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Faderl, I

INTERNATIONAL SEARCH REPORT

International Application No
PC1/GB 01/00038

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>FRIEBELE E J ET AL: "OPTICAL FIBER SENSORS FOR SPACECRAFT APPLICATIONS" SMART MATERIALS AND STRUCTURES, IOP PUBLISHING LTD., BRISTOL, GB, vol. 8, no. 6, December 1999 (1999-12), pages 813-838, XP000883621 ISSN: 0964-1726 page 813, column 2 page 817, paragraphs EMBEDDED-ISSUES page 818, column 1, paragraph 3 page 819, column 1, paragraph 2 page 820, column 2 page 821, paragraphs EMBEDDING-PROCESS page 822, column 2, paragraphs 2=4 ---</p>	1,11,33, 42,65
X	<p>EP 0 822 430 A (NIPPON TELEGRAPH & TELEPHONE) 4 February 1998 (1998-02-04) abstract; figures 21,26 page 10, line 37 -page 11, line 32 page 15, line 17 - line 25 ---</p>	1-4, 21-23, 28, 33-36, 51-53,65
A	<p>US 5 408 568 A (HAMILTON PHILLIP G B) 18 April 1995 (1995-04-18) the whole document ---</p>	6-8,38, 39
A	<p>US 5 555 330 A (PAN JING-JONG ET AL) 10 September 1996 (1996-09-10) abstract; figure 3A -----</p>	25,55

INTERNATIONAL SEARCH REPORT

International application No.
PCT/GB 01/00038

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:
1-11, 18-25, 28, 33-42, 49-56, 59, 64, 65

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-11,18-25,28,33-42,49-56,59,64,65

use of a laser to create a passageway in a composite material having an optical transition means embedded therein

2. Claims: 12-16,43-47

use of a depth marker to stop the drilling or machining process at a determined depth

3. Claims: 17,48

use of a thermal core expanded fiber to enhance coupling at the connection

4. Claims: 26-27,57-58

use of optical processing means on a micro-substrate

5. Claims: 29-32,60-63

use of evanescent coupling means to optically connect first and second transmission means

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PC1/GB 01/00038

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 2322479	A	26-08-1998	JP 10126018 A	15-05-1998
			DE 19781160 T	28-01-1999
			US 6257771 B	10-07-2001
			WO 9818301 A	30-04-1998

EP 0822430	A	04-02-1998	JP 10300961 A	13-11-1998
			KR 236432 B	15-12-1999
			US 5999670 A	07-12-1999

US 5408568	A	18-04-1995	GB 2273207 A,B	08-06-1994
			JP 6318906 A	15-11-1994

US 5555330	A	10-09-1996	EP 0799432 A	08-10-1997
			JP 10511476 T	04-11-1998
			WO 9619743 A	27-06-1996
			US 6198858 B	06-03-2001
			US 5652814 A	29-07-1997
			US 5642447 A	24-06-1997
			US 5642448 A	24-06-1997
			US 5889904 A	30-03-1999
			US 6023542 A	08-02-2000
